Datasheet

# PAS-IBS40W | Box Speaker with Twitter







## Key features

- Indoor wall-mounted box speaker designed for clear and pleasant sound.
- Multiple power tap settings for 70V, 100V, and 8Ω systems.
- Robust housing made of HIPS with a powder-coated iron mesh grill.
- Easy installation with a bracket and adjustable angle.
- Wide frequency response for versatile sound delivery.
- Comes in two color options: white and black.

## Product Overview

The PAS-IBS40W is a wall-mounted indoor box speaker providing clear, pleasant sound quality suitable for public spaces and meeting rooms. It features a frequency response of 80–20KHz and a sensitivity of 88dB ±3dB at 1 meter.

The speaker supports multiple power taps for 70V, 100V, and 8Ω installations, allowing flexible power usage up to 40W. Its durable housing is made from HIPS with a powder-coated iron mesh grill, and it includes a 6.5-inch woofer paired with a 1-inch silk dome tweeter. The unit is designed for easy installation with a mounting bracket and adjustable angle, available in both white and black finishes. Operating in temperatures from -25°C to 55°C.

## Technical Specification

| Feature | Details |
|---|---|
| Frequency Range | 80–20KHz |
| Sensitivity | 88dB ±3dB (1m/1W) |
| Power Rating | 40W |
| Power Tap Settings | 5W/10W/20W/40W @ 100V;<br>2.5W/5W/10W/20W/40W @ 70V;<br>40W @ 8Ω |
| Input Line Voltage | 100V / 70V |
| Housing Material | HIPS |
| Front Grill | Powder Coated Iron Mesh |
| Speaker Components | 6.5" Woofer + 1" Silk Dome |
| Available Colors | White / Black |
| Weight | 3.34kg |
| Dimensions (W x H x D) | 216mm × 299mm × 196mm |
| Operating Temperature | -25°C to 55°C |
| Certification | CE, RoHS Compliance |



©2024 Macsys

Macsys reserve rights to introduce modifications without notice. Product images are for illustrative purposes only, the actual product may vary. Warranty policy applies as described on our website.