Datasheet

# PAS-PLSB20W | Bi-directional Projector Speaker



## Key features

- IP55-rated, weather-resistant construction
- Robust aluminum housing for enhanced durability
- Integrated 20W transformer for flexible installation
- Bi-directional sound projection
- Wide 320° horizontal coverage
- Supports both 10W and 20W power settings

## Product Overview

The PAS-PLSB20W is a Bi-directional Projector Speaker 100v@20W designed for wall or corridor installation, offering reliable outdoor or indoor performance with an IP55 rating. Housed in a steady aluminum enclosure, it features a bi-directional sound projection and integrated 20W transformer for versatile use. It supports 10W and 20W power configurations, with a sensitivity of 92dB and a maximum SPL of 103dB.

The frequency response ranges from 110Hz to 15KHz, ensuring clear audio reproduction for voice and background music applications. With a 320-degree horizontal coverage and dual 6.5-inch full-range drivers, the PAS-PLSB20W provides extensive sound distribution. Its compact dimensions and 3.4kg weight make it suitable for a range of professional audio installations.

## Technical Specification

| Feature | Details |
|---|---|
| Model | PAS-PLSB20W |
| Power Handling | 10/20W |
| Rated Input Power | 5/10W |
| Sensitivity | 92dB |
| Maximum SPL | 103dB |
| Frequency Range | 110Hz~15KHz |
| Horizontal Coverage | 320 degree |
| Dimensions (Diameter x Length) | Dia 170×252mm |
| Mounting Application | Wall or corridor |
| Material | Aluminum |
| Weight | 3.4Kg |
| Color | White |
| Speaker Units | 6.5" ×2 full range |
| Certifications | CE, RoHS compliance |



©2024 Macsys

Macsys reserve rights to introduce modifications without notice. Product images are for illustrative purposes only, the actual product may vary. Warranty policy applies as described on our website.