Datasheet

PAS-PLSU20W | Unidirectional Projector Speaker



Key features

- Weather-resistant projector (IP 55)
- Durable aluminum construction
- Equipped with 20W transformer
- 120° wide dispersion
- Suitable for wall or ceiling mounting
- Delivers 103dB max SPL with 6.5" full-range driver

Product Overview

The PAS-PLSU20W is a Unidirectional Projector Speaker 100v@20W designed for demanding environments, featuring a durable aluminum enclosure and IP 55 rating for outdoor use. It comes with a built-in 20W transformer and supports both 10W and 20W power settings, delivering high performance at 92dB sensitivity and 103dB maximum SPL.

The speaker operates within a frequency range of 110Hz to 15KHz, ensuring clear and intelligible sound. With a wide 120-degree sound dispersion and 6.5" full-range driver, it achieves ample audio coverage for various applications. Its compact size (170×252mm) and versatile mounting options make it ideal for wall or ceiling installations. The lightweight 2.8Kg build and clean white finish further enhance its suitability for modern installations.

Technical Specification

Feature	Details
Power at 100V	10/20W
Power at 70V	5/10W
Sensitivity	92dB
Maximum output	103dB
Frequency response	110Hz~15KHz
Dispersion angle	120 degree
Dimensions	Dia 170×252mm
Installation type	Wall or ceiling
Housing material	Aluminum
Weight	2.8Kg
Finish color	White
Speaker size/type	6.5" ×1 full range
Certification	CE, RoHS Compliance

©2024 Macsys

Macsys reserve rights to introduce modifications without notice. Product images are for illustrative purposes only, the actual product may vary. Warranty policy applies as described on our website.