Datasheet

ACS-CC-KB | Camera Control Keyboard



Key features

- Wide protocol support: VISCA, PELCO D/P, ONVIF, VISCA over IP
- Mixed control via RS232/RS422/RS485 and IP
- Quick access to essential camera functions
- Variable-speed 4D joystick for smooth pan/tilt/zoom control
- Dual power input: DC 12V & PoE
- Up to 255 cameras can be controlled in one system
- Built-in LCD display with shortcut buttons for fast operation
- Supports automatic IP camera search & assignment
- Comfortable boat-type zoom switch for precision zoom
- Supports parameter configuration via IE browser

Product Overview

The Macsys ACS-CC-KB Camera Control Keyboard is a professional-grade controller designed for seamless management of PTZ and conference cameras. Supporting VISCA, PELCO D/P, ONVIF, and VISCA over IP protocols, it enables mixed protocol operation across RS232/422/485 and IP networks. With a variable-speed four-dimensional joystick, shortcut keys, and intuitive controls, it ensures precise camera handling. Dual power options (12V DC & PoE) provide flexibility, while its compatibility with up to 255 cameras makes it ideal for large-scale conference, broadcast, and surveillance applications.

Techinical Specification

Featues	Detail
Power Supply	DC 12V-2A (Inner Positive, Outer Negative) / PoE
Power Consumption	0.6W (Max)
Display	128 × 32 LCD
Buttons	Soft-touch silicone buttons
Joystick	Four-dimensional variable-speed control
Zoom Control	Boat-type switch
Audio Prompt	Key press sound notification (On/Off)
Supported Protocols	VISCA, ONVIF 2.4, PELCO D/P, VISCA over IP
Interfaces	1 × Ethernet Port, 1 × RS232 Port, 4 × RS-422/485 RJ-45 Ports, Tally/Contact Interface
Operating Temp.	0°C ~ 55°C (14°F ~ 131°F)
Storage Temp.	-10°C ~ 60°C (14°F ~ 140°F)
Operating Humidity	20% ~ 80% (Non-condensing)
Storage Humidity	0% ~ 90% (Non-condensing)
Dimensions	277.8 × 149.9 × 110.4 mm
Net Weight	1282 g
Certifications	CE, RoHS compliance

©2024 Macsys

Macsys reserve rights to introduce modifications without notice. Product images are for illustrative purposes only, the actual product may vary. Warranty policy applies as described on our website.